

SENSORS AND TRANSMITTERS

paladin 686 410 rfs



Overview

- Wireless door- / window contact sensor
- Transmission of open / closed status via RF
- Battery operated (battery lifetime approx. 12 years)
- KNX-RF 1.R S-Mode
- Test mode for a faster status request
- Compact housing
- Wall mounting / adhesive mounting

Programming note:

Everytime the ETS configuration is transferred to the device, the programming key need to be pressed!

Order numbers

■ paladin

686 410 rfs Door-/ window contact sensor

SENSORS AND TRANSMITTERS

paladin 686 410 rfs

Order information

	EAN	Art. No.
686 410 rfs	4022709239792	23979

Technical data

Supply voltage	battery operated 2 x 3 V CR2032 (included)
Battery lifetime	approx. 12 years
KNX medium	KNX RF 1.R
Application software	ETS5 or higher
Commissioning mode	system-mode (s-mode)
Radio frequency	868,3 Mhz
Transmission power	<10 dB
Range	in free field: 100 m indoors: approx. 30 m
Permitted ambient temperature	-10...+70 °C
Dimensions	sensor: 78 x 28 x 23 mm magnet: 60 x 16 x 12 mm
Mounting	fixed with adhesive strip or screws
Protection degree	IP 20

Rights to technical amendments reserved / Technische Änderungen vorbehalten
 Droits de modifications techniques réservés / Suscettibile di errori e modifiche

