

## KNX-RF COMPATIBLE PRODUCTS

### Motion- / presence detector paladin 674 110 rf



#### Overview

- Motion detector / presence detector for flush-ceiling mounting
- Two selectable operating modes (motion / presence detection)
- Coverage area Ø 7m at 2,5m installed height
- Battery operated (battery lifetime ~ 4 years)
- Compact housing
- Flush-ceiling mounting
- Protection degree IP20
- KNX-RF compatible

#### Order numbers

##### ■ paladin

674 110 rf	Motion detector / presence detector for flush-ceiling mounting
------------	----------------------------------------------------------------------

Technische Änderungen vorbehalten.

## KNX-RF COMPATIBLE PRODUCTS

### Motion- / presence detector paladin 674 110 rf

#### Technical data

Supply voltage	Battery operated 1x 3,6V LS14250 (included)
Battery lifetime	~ 4 years
Coverage area	360° Ø 7m at 2,5m installed height
Transmission type	Codified transmission in 868,4MHz with ERP>8mW and a coverage of 100m (in the free field)
Permitted ambient temperature	0°C...+45°C
Dimensions	Ø 80 mm (outside of housing) x Ø 65 mm (inner diameter) x 45 mm (depth)
Mounting	Flush-ceiling mounting (Ø 65-68 mm drill-hole)
Protection class	IP20

Technische Änderungen vorbehalten.

