

DIMMERS

paladin 683 831 rfs

**Overview**

- Dimmer for Building automation
- Dimming of LED strips up to 12 V - 48 V
- Maximum load 8A (12 V: 96 W, 24 V: 192 W)
- Minimum dimming level adjustable
- Control by pulse width modulation (PWM)
- KNX-RF 1.R S-mode
- Up to 5 Scenes can be stored / called up
- Staircase lighting timer function with (optional) advanced warning function
- Integrated cycle function
- Optional memory function of the last dimming value
- Additional connection for wired push-buttons
- RF-repeater function included
- Compact housing
- Flush-mounted fitting
- Protection degree IP20

Order numbers

■ paladin

683 831 rfs Dimmer LED strips
PWM up to 8A

DIMMERS

paladin 683 831 rfs

Order information

EAN	Art. No.
683 831 rfs	23924

Technical data

Supply voltage	12 V DC ... 48 V DC
Consumption	< 12mA
Switching capacity	12 V - 48 V DC / 8 A
KNX medium	KNX RF 1.R
Radio frequency	868,3 MHz
Transmission power	<10dBm
Range	in free field: 100m indoors: 30m
Numbers of outputs	1
Functions	dimming actuator timer / staircase lighting timer with optional advanced warning function signal repeater KNX-RF
Application software	ETS5 or higher
Commissioning mode	system-mode (s-mode)
Dimensions	46 x 46 x 30 mm
Mounting	flush-mounting
Operation temperature range	-10°C...+45°C
Connection	screw-type terminals
Degree of protection	IP20

Rights to technical amendments reserved / Technische Änderungen vorbehalten
 Droits de modifications techniques réservés / Suscettibile di errori e modifiche

